



**The Clorox Pet Products Company**  
 1221 Broadway  
 Oakland, CA 94612  
 Tel. 1-510-271-7000

# Material Safety Data Sheet

<b>I Product:</b> FRESH STEP® EXTREME ODOR CONTROL SCOOPABLE CLUMPING CAT LITTER													
<b>Description:</b> LIGHT AND DARK GRAY CLAY GRANULES WITH BLUE SPECKLES AND A WATERY, FLORAL ODOR													
	<b>Distributor</b>												
	The Clorox Sales Company 1221 Broadway Oakland, CA 94612												
	<b>Emergency Telephone Nos.</b>												
	For Medical Emergencies, call 1-800-446-1014.  For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).												
<b>II Health Hazard Data</b>	<b>III Hazardous Ingredients</b>												
<p>Inhalation of dust may irritate nose and throat.</p> <p>Cat feces can sometimes transmit a disease called toxoplasmosis. Pregnant women and immunosuppressed persons are most susceptible. Always remember to wash hands thoroughly after handling <b>used</b> cat litter. Unused cat litter poses no toxoplasmosis threat.</p> <p>Used cat litter is not recommended for use in the garden.</p> <p>No medical conditions are known to be aggravated by exposure to this product.</p> <p><b>FIRST AID:</b></p> <p><b>INHALATION:</b> Remove to fresh air. If breathing problems develop, call a doctor.</p> <p><b>EYE CONTACT:</b> Flush eyes with plenty of water for 15 minutes. If irritation persists, call a doctor.</p> <p><b>SKIN CONTACT:</b> Wash skin with water.</p> <p><b>INGESTION:</b> Drink a glassful of water. Call a doctor or poison control center.</p>	<table border="1"> <thead> <tr> <th>Ingredient</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Bentonite clay CAS # 1302-78-9</td> <td>&gt; 80%</td> <td>Not established.</td> </tr> <tr> <td>Calcium carbonate CAS # 1317-65-3</td> <td>3 - 10%</td> <td>10 mg/m<sup>3</sup> - TLV-TWA<sup>a</sup> (total dust) 15 mg/m<sup>3</sup> - PEL-TWA<sup>b</sup> (total dust) 5 mg/m<sup>3</sup> - PEL-TWA<sup>b</sup> (respirable fraction)</td> </tr> <tr> <td>Crystalline silica (quartz) CAS # 14808-60-7</td> <td>&lt; 6%</td> <td>0.05 mg/m<sup>3</sup> - TLV-TWA<sup>a</sup> (respirable fraction)</td> </tr> </tbody> </table> <p><sup>a</sup>TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average  <sup>b</sup>PEL-TWA = OSHA Permissible Exposure Limit - Time Weighted Average</p> <p>IARC Monographs (Volume 68, 1997) state that there is sufficient evidence of the carcinogenicity of inhaled crystalline silica (quartz) from occupational sources in humans. IARC classification - Group 1.</p> <p>None of the other materials in this product are on the IARC, OSHA, or NTP carcinogen lists.</p>	Ingredient	Concentration	Worker Exposure Limit	Bentonite clay CAS # 1302-78-9	> 80%	Not established.	Calcium carbonate CAS # 1317-65-3	3 - 10%	10 mg/m <sup>3</sup> - TLV-TWA <sup>a</sup> (total dust) 15 mg/m <sup>3</sup> - PEL-TWA <sup>b</sup> (total dust) 5 mg/m <sup>3</sup> - PEL-TWA <sup>b</sup> (respirable fraction)	Crystalline silica (quartz) CAS # 14808-60-7	< 6%	0.05 mg/m <sup>3</sup> - TLV-TWA <sup>a</sup> (respirable fraction)
Ingredient	Concentration	Worker Exposure Limit											
Bentonite clay CAS # 1302-78-9	> 80%	Not established.											
Calcium carbonate CAS # 1317-65-3	3 - 10%	10 mg/m <sup>3</sup> - TLV-TWA <sup>a</sup> (total dust) 15 mg/m <sup>3</sup> - PEL-TWA <sup>b</sup> (total dust) 5 mg/m <sup>3</sup> - PEL-TWA <sup>b</sup> (respirable fraction)											
Crystalline silica (quartz) CAS # 14808-60-7	< 6%	0.05 mg/m <sup>3</sup> - TLV-TWA <sup>a</sup> (respirable fraction)											
<b>IV Special Protection and Precautions</b>	<b>V Transportation and Regulatory Data</b>												
<p><b>Hygienic Practices:</b> Wash hands after direct contact.</p> <p><b>Engineering Controls:</b> Use general ventilation to minimize exposure to dust.</p> <p><b>Personal Protective Equipment:</b> In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.</p> <p>Particles may scratch hard surfaces, such as vinyl flooring.</p> <p>Do not use this product as a traction aid because product becomes slippery and slick when wet.</p>	<p><b>DOT/IATA/IMDG:</b> Not restricted.</p> <p><b>EPA - SARA Title III/CERCLA:</b> This product is regulated under Sections 311/312. This product contains no chemicals regulated under Section 313 or under Section 304/CERCLA.</p> <p><b>TSCA 8(b):</b> All components of this product are either on the TSCA 8(b) Inventory or otherwise exempt from listing.</p> <p><b>TSCA 12(b):</b> This product is not subject to TSCA 12(b) reporting requirements.</p>												
<b>VI Spill Procedures/Waste Disposal</b>	<b>VII Reactivity Data</b>												
<p><b>Spill Procedures:</b> Vacuum sweep, if possible, to avoid generating airborne dust. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.</p> <p><b>Waste Disposal:</b> Reclaim, if possible, since material may be used as an absorbent for liquid spills. Otherwise, dispose of in accordance with all applicable federal, state, and local regulations.</p>	<p>Stable under normal use and storage conditions.</p>												
<b>VIII Fire and Explosion Data</b>	<b>IX Physical Data</b>												
<p>Not flammable or explosive.</p>	<p>Bulk density (g/cm<sup>3</sup>) ..... ~1.1</p> <p>Solubility in water ..... Insoluble</p>												