

**The Armor All/STP Products Company**1221 Broadway  
Oakland, CA 94612  
Tel. (510) 271-7000**Material Safety  
Data Sheet**

<b>I Product:</b> ARMOR ALL® WHEEL PROTECTANT																	
<b>Description:</b> CLEAR, COLORLESS, THIN LIQUID WITH A MILD SOLVENT ODOR IN AN AEROSOL CAN																	
<b>Other Designations</b>	<b>Distributor</b>	<b>Emergency Telephone Nos.</b>															
	The Armor All/STP Products Company 1221 Broadway Oakland, CA 94612	For Medical Emergencies, call 1-800-446-1014.  For Transportation Emergencies, call 1-800-424-9300 (Chemtrec).															
<b>II Health Hazard Data</b>		<b>III Hazardous Ingredients</b>															
<p>May cause mild eye and skin irritation. Prolonged inhalation of propellant may cause symptoms of central nervous system depression including headache, dizziness, nausea, loss of balance, and drowsiness.</p> <p>No medical conditions are known to be aggravated by exposure to this product.</p> <p><b>FIRST AID:</b></p> <p><b>EYE CONTACT:</b> Rinse with plenty of water. If irritation persists, call a doctor.</p> <p><b>SKIN CONTACT:</b> Wash with soap and water. If irritation persists, call a doctor.</p> <p><b>INGESTION:</b> Drink a glassful of water. Immediately call a doctor or poison control center.</p> <p><b>INHALATION:</b> Remove to fresh air. If breathing problems develop, call a doctor.</p>		<table border="1"> <thead> <tr> <th>Ingredients</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Decamethylcyclpentasiloxane CAS # 541-02-6</td> <td>40 - 60%</td> <td>Not established.</td> </tr> <tr> <td>Triethoxyoctylsilane CAS # 2943-75-1</td> <td>1 - 5%</td> <td>Not established.</td> </tr> <tr> <td>Propane CAS # 74-98-6</td> <td>5 - 10%</td> <td>1000 ppm - TLV-TWA<sup>a,b</sup> 1000 ppm - PEL<sup>c</sup></td> </tr> <tr> <td>Isobutane CAS # 75-28-5</td> <td>35 - 50%</td> <td>1000 ppm TLV-TWA<sup>a,b</sup></td> </tr> </tbody> </table> <p><sup>a</sup>TLV-TWA = ACGIH Threshold Limit Value-Time Weighted Average  <sup>b</sup>ACGIH TLV-TWA for aliphatic hydrocarbon gases (C1-C4 alkanes)  <sup>c</sup>PEL = OSHA Permissible Exposure Limit - Time Weighted Average</p> <p>None of the ingredients in the product are on the IARC, NTP, or OSHA carcinogen lists.</p>	Ingredients	Concentration	Worker Exposure Limit	Decamethylcyclpentasiloxane CAS # 541-02-6	40 - 60%	Not established.	Triethoxyoctylsilane CAS # 2943-75-1	1 - 5%	Not established.	Propane CAS # 74-98-6	5 - 10%	1000 ppm - TLV-TWA <sup>a,b</sup> 1000 ppm - PEL <sup>c</sup>	Isobutane CAS # 75-28-5	35 - 50%	1000 ppm TLV-TWA <sup>a,b</sup>
Ingredients	Concentration	Worker Exposure Limit															
Decamethylcyclpentasiloxane CAS # 541-02-6	40 - 60%	Not established.															
Triethoxyoctylsilane CAS # 2943-75-1	1 - 5%	Not established.															
Propane CAS # 74-98-6	5 - 10%	1000 ppm - TLV-TWA <sup>a,b</sup> 1000 ppm - PEL <sup>c</sup>															
Isobutane CAS # 75-28-5	35 - 50%	1000 ppm TLV-TWA <sup>a,b</sup>															
<b>IV Special Protection and Precautions</b>		<b>V Transportation and Regulatory Data</b>															
<p><b>Hygienic Practices:</b> Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods.</p> <p><b>Engineering Controls:</b> Use general ventilation to minimize exposure to product vapor.</p> <p><b>Personal Protective Equipment:</b> Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.</p> <p>Contents under pressure. Do not expose to heat or store at temperatures above 120°F. Do not puncture or incinerate container. Store in accordance with NFPA 30B for Level 3 aerosols.</p>		<p><b>DOT:</b> Consumer Commodity ORM-D.</p> <p><b>IMDG:</b> Aerosols, flammable, n.o.s., Class 2.1; UN1950; limited quantity.</p> <p><b>IATA:</b> Aerosols, flammable, n.o.s., Class 2.1; UN1950.</p> <p><b>EPA - SARA Title III/CERCLA:</b> This product is regulated under Sections 311/312. This product contains no chemicals that are regulated under Section 313 or under Section 304/CERCLA.</p>															
<b>VI Spill Procedures/Waste Disposal</b>		<b>VII Reactivity Data</b>															
<p><b>Spill Procedures:</b> Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.</p> <p><b>Waste Disposal:</b> Dispose of in accordance with all applicable federal, state, and local regulations.</p>		Stable under normal use and storage conditions.															
<b>VIII Fire and Explosion Data</b>		<b>IX Physical Data</b>															
<p><b>Flashpoint:</b> 79°C (closed cup) for liquid</p> <p><b>Flame extension:</b> 14 inches with flashback.</p> <p><b>Fire Extinguishing Agents:</b> Dry chemical, carbon dioxide (CO<sub>2</sub>), foam, or water spray.</p> <p><b>Fire and Explosion Hazards:</b> Containers may rupture at temperatures &gt;120°F.</p> <p><b>NFPA Aerosol Classification:</b> Level 3.</p> <p><b>CPSC Aerosol Classification:</b> Flammable.</p>		<p>pH..... N/A</p> <p>Specific gravity ..... ~0.96</p> <p>Solubility in water..... Slight</p>															